



2021
CFORCE 400
EPS LX (2 UP)

STARTING AT
\$7,999*

BEST
5
YEAR
LIMITED WARRANTY

FOLLOW US   

CFMOTO.CA

* The price indicated does not include registration, transport, preparation fees, the cost of accessories and the installation thereof. Applicable taxes not include. Photos are for illustrative purposes only and any accessories shown are not included. Specifications to change without notice. Details in store.

CFORCE 400

EPS LX (2 UP)

FREE
MORE THAN \$4,500
IN FREE ADD-ONS!

THE MOST EQUIPPED VEHICLES ON THE MARKET

STANDARD FEATURES AND BENEFITS

5-year CFMOTO warranty
\$3,300 Value

2,500 lbs winch
(Complete assy)
\$490 Value

Safety and convenience package
including:

- Lateral mirrors
- Trailer connector
- Anti-theft (gear lever lock)
- Double USB plug
- 12V outlet
- Flashers
- Horn

\$283 Value

Skid plate
and triangular arm protector
\$250 Value

Steel front bumper
\$169 Value

Hitch receiver
\$103 Value

BEST
5 YEAR
LIMITED WARRANTY

CF MOTO WARRANTY

CFMOTO Canada's standard 5-year warranty includes a 12-month manufacturer limited warranty and a 48-month powertrain limited warranty.

5 Year limited warranty: 1 year full + balance
48 months powertrain only or 5,000 km.

AVAILABLE
COLOR



Electric Power
Steering



Lateral Mirrors



12V outlet



CVTech Clutch
System

SPECIFICATIONS

ENGINE

Type: Single-Cylinder, 4-valves, 4 strokes

Displacement: 400 cc

Engine management: BOSCH EFI
& Ignition

Maximum torque: 24.3 FT/LB @ 6000 rpm

Maximum power output: 30.5 HP / 7200
rpm

Cooling system: Liquid

Starting: Electric

Battery: 30 Amp

SIZE / WEIGHT

Length x width x height: 2305 x 1100
x 1350 mm (90.7 x 43.3 x 53.1 in)

Wheelbase: 1460 mm (57.5 in)

Ground clearance: 250 mm (9.8 in)

Fuel tank capacity: 14 L (3.70 gal)

Weight with all fluids: 358 kg (789 lbs)

Front/Rear rack capacity: 20 kg (44 lbs) /
40 kg (88 lbs)

BRAKES

Brakes: Front and rear brake disc system

WHEELS

Front wheels: Aluminum wheel alloy
(12 x 6 in)

Rear wheels: Aluminum wheel alloy
(12 x 7.5 in)

Front tires: AT 25 x 8-12
(Innova Mud Gear Lite 6 ply rating)

Rear tires: AT 25 x 10-12
(Innova Mud Gear Lite 6 ply rating)

TRANSMISSION

CV-Tech IBC clutch system: Primary
and secondary variable transmission

Gear box: L / H / N / R / P
(parking lock shift system)

Power train: 2 wheel / 4 wheel drive,
electric locking differential

SUSPENSION AND STEERING

Front suspension: Double arm
independent suspension, Hydraulic
shock absorber, five adjustments spring
preloads

Front travel: 170 mm (6.7 in)

Rear suspension: Double arm
independent suspension, Hydraulic
shock absorber, five adjustments spring
preloads

Rear travel: 170 mm (6.7 in)

Steering: Electric Power Steering (EPS)

CFMOTO.CA

For additional information, please contact your nearest dealer.